

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

### SECTION 1. IDENTIFICATION

Product name : CAL BRONZE LEAD FREE  
SDS-Identcode : 302G

#### Manufacturer or supplier's details

Company name of supplier : Bestolife Corporation  
Address : 2777 N. Stemmons Frwy Ste 1800  
Dallas TX 75207,  
Telephone : 855-243-9164/972-865-8961  
Telefax : 214-631-3047  
Emergency telephone : CHEMTREC U.S.: 800-424-9300, International 703-527-3887  
(24-hours/7 days)  
E-mail address : www.bestolife.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Industrial use  
Thread Compound (Pipe Dope) and Jacking grease for use in  
Offshore industries  
Mining, (without offshore industries)  
Restrictions on use : Do not use on oxygen lines or in oxygen enriched atmos-  
pheres.


---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Eye irritation : Category 2A

#### GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.

Precautionary Statements : **Prevention:**  
P264 Wash skin thoroughly after handling.  
P280 Wear eye protection/ face protection.  
**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water  
for several minutes. Remove contact lenses, if present and easy  
to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ atten-  
tion.

---

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

| Chemical name   | CAS-No.    | Concentration (% w/w) |
|---|------------|-----------------------|
| Distillates (petroleum), hydrotreated heavy naphthenic                | 64742-52-5 | >= 50 - < 70          |
| Graphite  | 7782-42-5  | >= 10 - < 20          |
| Talc  | 14807-96-6 | >= 10 - < 20          |
| Copper metal powder   | 7440-50-8  | >= 5 - < 10           |
| Dolomite  | 16389-88-1 | >= 1 - < 5            |
| Calcium oxide   | 1305-78-8  | >= 1 - < 5            |
| 12-Hydroxy lithium stearate   | 7620-77-1  | >= 1 - < 5            |
| Quartz  | 14808-60-7 | >= 1 - < 5            |
| Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) | 57855-77-3 | >= 1 - < 5            |

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.
- Notes to physician : Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

- Unsuitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
  - Specific hazards during fire fighting : None known.
  - Hazardous combustion products : Exposure to combustion products may be a hazard to health.  
Carbon oxides  
Metal oxides  
Silicon oxides
  - Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.
  - Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.
- 

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.
  - Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.
  - Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
- 

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Advice on safe handling : Do not get on skin or clothing.  
Do not swallow.  
Do not get in eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
 Date of first issue: 05/12/2015

Materials to avoid : Store in accordance with the particular national regulations.  
 : Do not store with the following product types:  
 Strong oxidizing agents

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components   | CAS-No.    | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis     |
|--|------------|-------------------------------|--|-----------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | TWA (Mist)                    | 5 mg/m <sup>3</sup>                            | OSHA Z-1  |
|  |            | TWA (Inhalable fraction)      | 5 mg/m <sup>3</sup>                            | ACGIH     |
|  |            | TWA (Mist)                    | 5 mg/m <sup>3</sup>                            | NIOSH REL |
|  |            | ST (Mist)                     | 10 mg/m <sup>3</sup>                           | NIOSH REL |
| Graphite   | 7782-42-5  | TWA (Respirable)              | 2.5 mg/m <sup>3</sup>                          | NIOSH REL |
|  |            | TWA (Respirable fraction)     | 2 mg/m <sup>3</sup>                            | ACGIH     |
|  |            | TWA (Dust)                    | 15 Million particles per cubic foot            | OSHA Z-3  |
| Talc   | 14807-96-6 | TWA (Dust)                    | 20 Million particles per cubic foot            | OSHA Z-3  |
|  |            | TWA (Respirable)              | 2 mg/m <sup>3</sup>                            | NIOSH REL |
|  |            | TWA (Respirable fraction)     | 2 mg/m <sup>3</sup>                            | ACGIH     |
|  |            | TWA (Dust and mist)           | 1 mg/m <sup>3</sup> (Copper)                   | ACGIH     |
| Copper metal powder                                    | 7440-50-8  | TWA (Fumes)                   | 0.2 mg/m <sup>3</sup> (Copper)                 | ACGIH     |
|  |            | TWA (Dust)                    | 1 mg/m <sup>3</sup> (Copper)                   | NIOSH REL |
|  |            | TWA (Mist)                    | 1 mg/m <sup>3</sup> (Copper)                   | NIOSH REL |
|  |            | TWA (dusts and mists)         | 1 mg/m <sup>3</sup> (Copper)                   | OSHA Z-1  |
|  |            | TWA (Fumes)                   | 0.1 mg/m <sup>3</sup> (Copper)                 | OSHA Z-1  |
|  |            | TWA (Respirable)              | 5 mg/m <sup>3</sup> (Calcium carbonate)        | NIOSH REL |
|  |            | TWA (total)                   | 10 mg/m <sup>3</sup> (Calcium carbonate)       | NIOSH REL |
| Calcium oxide  | 1305-78-8  | TWA                           | 2 mg/m <sup>3</sup>                            | ACGIH     |
|  |            | TWA                           | 2 mg/m <sup>3</sup>                            | NIOSH REL |

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
 Date of first issue: 05/12/2015

|                             |            |                           |   |           |
|-----------------------------|------------|---------------------------|---|-----------|
|                             |            | TWA                       | 5 mg/m <sup>3</sup>                         | OSHA Z-1  |
| 12-Hydroxy lithium stearate | 7620-77-1  | TWA (Inhalable fraction)  | 10 mg/m <sup>3</sup>                        | ACGIH     |
|                             |            | TWA (Respirable fraction) | 3 mg/m <sup>3</sup>                         | ACGIH     |
| Quartz                      | 14808-60-7 | TWA (Respirable dust)     | 0.05 mg/m <sup>3</sup>                      | OSHA Z-1  |
|                             |            | TWA (respirable)          | 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 | OSHA Z-3  |
|                             |            | TWA (respirable)          | 250 mppcf / %SiO <sub>2</sub> +5            | OSHA Z-3  |
|                             |            | TWA (Respirable fraction) | 0.025 mg/m <sup>3</sup> (Silica)            | ACGIH     |
|                             |            | TWA (Respirable dust)     | 0.05 mg/m <sup>3</sup> (Silica)             | NIOSH REL |

**These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.**

Quartz

**Engineering measures** : Minimize workplace exposure concentrations. Dust formation may be relevant in the processing of this product. In addition to substance-specific OELs, general limitations of concentrations of particulates in the air at workplaces have to be considered in workplace risk assessment. Relevant limits include: OSHA PEL for Particulates Not Otherwise Regulated of 15 mg/m<sup>3</sup> - total dust, 5 mg/m<sup>3</sup> - respirable fraction; and ACGIH TWA for Particles (insoluble or poorly soluble) Not Otherwise Specified of 3 mg/m<sup>3</sup> - respirable particles, 10 mg/m<sup>3</sup> - inhalable particles.

**Personal protective equipment**

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often!

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous semi-solid  
Color : copper, black  
Odor : Petroleum  
Odor Threshold : No data available

pH : Not applicable (not an aqueous solution)

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available  
Flash point :  $\geq 392$  °F /  $\geq 200$  °C

Method: ASTM D 92, Cleveland open cup  
Distillates (petroleum), hydrotreated heavy naphthenic

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : 1.2

Solubility(ies)  
Water solubility : negligible

Partition coefficient: n-octanol/water : Not applicable

**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, kinematic : Not applicable

Flow time : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.

Conditions to avoid : None known.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

---

**CAL BRONZE LEAD FREE**

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

Remarks: Based on data from similar materials

**Graphite:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

**Talc:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

**Copper metal powder:**

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg  
Method: OECD Test Guideline 423  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.11 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 436  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

**Dolomite:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal



**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

toxicity  
 Remarks: Based on data from similar materials

**Calcium oxide:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
 Method: OECD Test Guideline 425

Acute inhalation toxicity : (Rat): > 5 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: OECD Test Guideline 436  
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,500 mg/kg  
 Method: OECD Test Guideline 402  
 Assessment: The substance or mixture has no acute dermal toxicity  
 Remarks: Based on data from similar materials

**12-Hydroxy lithium stearate:**

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
 Assessment: The substance or mixture has no acute oral toxicity

**Quartz:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Acute oral toxicity : LD50 (Rat): > 2,500 mg/kg  
 Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
 Remarks: Based on data from similar materials

**Skin corrosion/irritation**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rabbit  
 Result : No skin irritation  
 Remarks : Based on data from similar materials

**Graphite:**

Species : Rabbit  
 Method : OECD Test Guideline 404  
 Result : No skin irritation

**Talc:**

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

Species : Rabbit  
Result : No skin irritation

### Copper metal powder:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Dolomite:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Calcium oxide:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Based on data from similar materials

### 12-Hydroxy lithium stearate:

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

### Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Product:

Result : Irritation to eyes, reversing within 21 days

### Components:

#### Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

#### Graphite:

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

**Talc:**

Species : Rabbit  
 Result : No eye irritation

**Copper metal powder:**

Species : Rabbit  
 Result : No eye irritation  
 Method : OECD Test Guideline 405

**Dolomite:**

Species : Rabbit  
 Result : No eye irritation  
 Method : OECD Test Guideline 405  
 Remarks : Based on data from similar materials

**Calcium oxide:**

Species : Rabbit  
 Result : Irreversible effects on the eye  
 Method : OECD Test Guideline 405

**12-Hydroxy lithium stearate:**

Species : Rabbit  
 Result : No eye irritation  
 Remarks : Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Species : Rabbit  
 Result : Irritation to eyes, reversing within 21 days  
 Remarks : Based on data from similar materials

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Test Type : Buehler Test  
 Routes of exposure : Skin contact  
 Species : Guinea pig  
 Result : negative  
 Remarks : Based on data from similar materials

**Graphite:**

Test Type : Local lymph node assay (LLNA)  
 Routes of exposure : Skin contact

**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

Species : Mouse  
 Result : negative

**Talc:**

Routes of exposure : Skin contact  
 Species : Humans  
 Result : negative

**Copper metal powder:**

Test Type : Maximization Test  
 Routes of exposure : Skin contact  
 Species : Guinea pig  
 Method : OECD Test Guideline 406  
 Result : negative

**Dolomite:**

Test Type : Local lymph node assay (LLNA)  
 Routes of exposure : Skin contact  
 Species : Mouse  
 Method : OECD Test Guideline 429  
 Result : negative  
 Remarks : Based on data from similar materials

**Calcium oxide:**

Test Type : Local lymph node assay (LLNA)  
 Routes of exposure : Skin contact  
 Species : Mouse  
 Method : OECD Test Guideline 429  
 Result : negative  
 Remarks : Based on data from similar materials

**12-Hydroxy lithium stearate:**

Test Type : Local lymph node assay (LLNA)  
 Routes of exposure : Skin contact  
 Species : Mouse  
 Method : OECD Test Guideline 429  
 Result : negative

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Test Type : Human repeat insult patch test (HRIPT)  
 Routes of exposure : Skin contact  
 Result : negative

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

**CAL BRONZE LEAD FREE**

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

Genotoxicity in vivo : Method: OECD Test Guideline 471  
Result: negative  
: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Graphite:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

**Talc:**

Genotoxicity in vitro : Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative  
Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Rat  
Application Route: Ingestion  
Result: negative

**Copper metal powder:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: Directive 67/548/EEC, Annex V, B.12.  
Result: negative  
Remarks: Based on data from similar materials

**Dolomite:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative  
Remarks: Based on data from similar materials

**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

**Calcium oxide:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative

Test Type: Chromosome aberration test in vitro  
 Method: OECD Test Guideline 473  
 Result: negative  
 Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
 Method: OECD Test Guideline 476  
 Result: negative  
 Remarks: Based on data from similar materials

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
 Method: OECD Test Guideline 471  
 Result: negative  
 Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Product:**

Carcinogenicity - Assessment : Petroleum distillates have been classified as not carcinogenic based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Mouse  
 Application Route : Skin contact  
 Exposure time : 78 weeks  
 Method : OECD Test Guideline 451  
 Result : negative

**Talc:**

Species : Mouse  
 Application Route : inhalation (dust/mist/fume)  
 Exposure time : 2 Years  
 Result : negative

**Calcium oxide:**

Species : Rat  
 Application Route : Ingestion  
 Exposure time : 104 weeks  
 Result : negative  
 Remarks : Based on data from similar materials

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

### Quartz:

Species : Humans  
Application Route : inhalation (dust/mist/fume)  
Result : positive  
Remarks : IARC: (International Agency for Research on Cancer)  
These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

**IARC**      Group 1: Carcinogenic to humans  
Quartz      14808-60-7  
(Silica dust, crystalline)

**OSHA**      No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**      Known to be human carcinogen  
Quartz      14808-60-7  
(Silica, Crystalline (Respirable Size))

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Graphite:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative

#### Talc:

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

#### Copper metal powder:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rabbit  
Application Route: Ingestion  
Result: negative

### **Dolomite:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

### **Calcium oxide:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

### **STOT-single exposure**

Not classified based on available information.

### **Components:**

#### **Calcium oxide:**

Assessment : May cause respiratory irritation.

### **STOT-repeated exposure**

Not classified based on available information.



**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

**Components:****12-Hydroxy lithium stearate:**

Routes of exposure : Ingestion  
 Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

**Quartz:**

Routes of exposure : inhalation (dust/mist/fume)  
 Target Organs : Lungs  
 Assessment : Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

**Repeated dose toxicity****Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Species : Rat  
 NOAEL : > 0.98 mg/l  
 Application Route : inhalation (dust/mist/fume)  
 Exposure time : 28 Days  
 Remarks : Based on data from similar materials

**Copper metal powder:**

Species : Rat  
 NOAEL :  $\geq 2 \text{ mg/m}^3$   
 Application Route : inhalation (dust/mist/fume)  
 Exposure time : 28 Days

**Dolomite:**

Species : Mouse  
 NOAEL : 1,300 mg/kg  
 Application Route : Ingestion  
 Exposure time : 28 Days  
 Remarks : Based on data from similar materials

**Calcium oxide:**

Species : Rat  
 NOAEL :  $\geq 0.399 \text{ mg/l}$   
 Application Route : inhalation (dust/mist/fume)  
 Exposure time : 90 Days  
 Method : OECD Test Guideline 413

**12-Hydroxy lithium stearate:**

Species : Rat  
 NOAEL : > 88 mg/kg  
 Application Route : Ingestion  
 Exposure time : 90 Days

**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

**Quartz:**

|                   |   |   |
|-------------------|---|---|
| Species           | : | Humans  |
| LOAEL             | : | 0.053 mg/m <sup>3</sup>   |
| Application Route | : | inhalation (dust/mist/fume)   |
| Remarks           | : | These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard. |

**Aspiration toxicity**

Not classified based on available information.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

|                  |   |  |
|------------------|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 1,064,120 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203<br>Remarks: Based on data from similar materials |
|------------------|---|--|

|   |   |   |
|---|---|---|
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 16,410 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 202<br>Remarks: Based on data from similar materials |
|---|---|---|

|  |   |   |
|--|---|---|
|  | : | EC50 (Daphnia magna (Water flea)): 32,820 mg/l<br>Exposure time: 48 h<br>Method: OECD Test Guideline 202<br>Remarks: Based on data from similar materials |
|--|---|---|

|                   |   |   |
|-------------------|---|---|
| Toxicity to algae | : | EC50 (Selenastrum capricornutum (green algae)): 110,268 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 201<br>Remarks: Based on data from similar materials |
|-------------------|---|---|

|  |   |   |
|--|---|---|
|  | : | NOEC (Selenastrum capricornutum (green algae)): 100 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 201<br>Remarks: Based on data from similar materials |
|--|---|---|

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

|                  |   |  |
|------------------|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l<br>Exposure time: 96 h<br>Method: OECD Test Guideline 203<br>Remarks: Based on data from similar materials |
|------------------|---|--|

|   |   |  |
|---|---|--|
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 10,000 mg/l<br>Exposure time: 48 h<br>Remarks: Based on data from similar materials |
|---|---|--|

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l  
Exposure time: 10 min  
Remarks: Based on data from similar materials

### Graphite:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae : EL50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
  
NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,012.5 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

### Talc:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 100,000 mg/l  
Exposure time: 24 h

### Copper metal powder:

Toxicity to fish : LC50: > 10 - 100 µg/l  
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC: > 1 - 10 µg/l

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

### **Dolomite:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 16.6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 16.6 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility.  
Based on data from similar materials
- Toxicity to algae : NOEC (Desmodesmus subspicatus (green algae)): 14 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

### **Calcium oxide:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials
- Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- EC10 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Crangon crangon (shrimp)): > 1 mg/l  
Exposure time: 14 d  
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EC50: > 100 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209  
Remarks: Based on data from similar materials

### **12-Hydroxy lithium stearate:**

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l  
Exposure time: 96 h

**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to algae : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201

**Quartz:****Ecotoxicology Assessment**

Acute aquatic toxicity : No toxicity at the limit of solubility.

Chronic aquatic toxicity : No toxicity at the limit of solubility.

**Calcium bis(di C8-C10, branched, C9 rich, alkyl naphthalenesulphonate):**

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l  
 Exposure time: 96 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
 Exposure time: 48 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 202  
 Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10: 110 mg/l  
 Exposure time: 3 h  
 Method: OECD Test Guideline 209  
 Remarks: Based on data from similar materials

**Persistence and degradability****Product:**

Biodegradability : Result: Readily biodegradable.  
 Remarks: Based on data from similar materials

**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

**12-Hydroxy lithium stearate:**

Biodegradability : Result: Readily biodegradable.

**CAL BRONZE LEAD FREE**

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

Biodegradation: 78 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301C

**Calcium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate):**

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 16 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B  
 Remarks: Based on data from similar materials

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.  
 Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
 Empty containers retain residue and can be dangerous.  
 Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
 If not otherwise specified: Dispose of as unused product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 3077  
 Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
 (Copper metal powder)  
 Class : 9  
 Packing group : III  
 Labels : 9

**IATA-DGR**

UN/ID No. : UN 3077  
 Proper shipping name : Environmentally hazardous substance, solid, n.o.s.  
 (Copper metal powder)  
 Class : 9  
 Packing group : III  
 Labels : Miscellaneous  
 Packing instruction (cargo) : 956

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

aircraft)  
Packing instruction (passenger aircraft) : 956  
Environmentally hazardous : yes

### IMDG-Code

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Copper metal powder)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3077  
Proper shipping name : Environmentally hazardous substance, solid, n.o.s. (Copper metal powder)  
Class : 9  
Packing group : III  
Labels : CLASS 9  
ERG Code : 171  
Marine pollutant : yes(Copper metal powder)  
Remarks : Above applies only to containers over 119 gallons or 450 liters.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

| Components          | CAS-No.   | Component RQ (lbs) | Calculated product RQ (lbs) |
|---------------------|-----------|--------------------|-----------------------------|
| Copper metal powder | 7440-50-8 | 5000               | 68493                       |

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Serious eye damage or eye irritation

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

---

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

|                     |           |               |
|---------------------|-----------|---------------|
| Copper metal powder | 7440-50-8 | >= 5 - < 10 % |
|---------------------|-----------|---------------|

### US State Regulations

#### Pennsylvania Right To Know

|  |            |
|--|------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 |
| Graphite   | 7782-42-5  |
| Talc   | 14807-96-6 |
| Copper metal powder                                    | 7440-50-8  |
| Dolomite   | 16389-88-1 |
| Calcium oxide  | 1305-78-8  |
| Quartz   | 14808-60-7 |

#### California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

|  |            |
|--|------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 |
| Graphite   | 7782-42-5  |
| Talc   | 14807-96-6 |
| Copper metal powder                                    | 7440-50-8  |
| Calcium oxide  | 1305-78-8  |

#### California Permissible Exposure Limits for Chemical Contaminants

|  |            |
|--|------------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 |
| Graphite   | 7782-42-5  |
| Talc   | 14807-96-6 |
| Copper metal powder                                    | 7440-50-8  |
| Calcium oxide  | 1305-78-8  |
| Quartz   | 14808-60-7 |

#### California Regulated Carcinogens

|        |            |
|--------|------------|
| Quartz | 14808-60-7 |
|--------|------------|

#### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

AICS : All ingredients listed or exempt.




## CAL BRONZE LEAD FREE

Version 8.2      Revision Date: 10/08/2018      SDS Number: 115216-00016      Date of last issue: 10/01/2018  
Date of first issue: 05/12/2015

## SECTION 16. OTHER INFORMATION

## Further information

## NFPA 704:



## HMIS® IV:

|                 |   |   |
|-----------------|---|---|
| HEALTH          | / | 2 |
| FLAMMABILITY    |   | 1 |
| PHYSICAL HAZARD |   | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

|                 |   |   |
|-----------------|---|---|
| ACGIH           | : | USA. ACGIH Threshold Limit Values (TLV)   |
| NIOSH REL       | : | USA. NIOSH Recommended Exposure Limits  |
| OSHA Z-1        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants          |
| OSHA Z-3        | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts                        |
| ACGIH / TWA     | : | 8-hour, time-weighted average   |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| NIOSH REL / ST  | : | STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday    |
| OSHA Z-1 / TWA  | : | 8-hour time weighted average  |
| OSHA Z-3 / TWA  | : | 8-hour time weighted average  |

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Oth-

# SAFETY DATA SHEET



## CAL BRONZE LEAD FREE

|         |                |              |                                 |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number:  | Date of last issue: 10/01/2018  |
| 8.2     | 10/08/2018     | 115216-00016 | Date of first issue: 05/12/2015 |

---

erwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/08/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8